

IN THE CLAIMS: // /

Please cancel Claims 2, 13 and 15.

Please amend Claims 1, 3, 9-12 and 25:

1. A tamper indicating closure configured for snap-on or screw-on application to a container, said closure comprising:

- a. a closure top portion;
- b. an annular depending skirt extending from said top portion, said depending skirt having an internal thread configuration adapted for engaging an external thread configuration on the neck portion of said container by snap-on application during initial installation of said closure to ~~said~~ the container neck;
- c. an inner annular sealing flange depending from said closure top portion in spaced relation to said depending skirt; and
- d. a tamper indicating ring connected to said depending skirt by a plurality of frangible elements;

wherein said tamper indicating ring includes at least one arcuate projection extending around at least a portion of said tamper indicating ring arranged for registration with a container neck portion on which said closure is positioned and said closure includes at least one nonremovable member breakably attached to said tamper-indicating ring which cooperates with at least one said arcuate projection to assist in breaking said tamper indicating ring during removal of said closure from said container neck.; and

wherein at least one said arcuate projection is held in place by an annular locking flange on ~~said the~~ container neck as said member is pulled away from said arcuate projection by twist-off removal of said annular depending skirt to cause said tamper indicating ring to break at a weakened area as said member pulls said tamper indicating ring upward to cause breakage of ~~said~~ frangible elements connecting said skirt to said tamper indicating ring and fracture of said weakened area by separation of said portion of said tamper indicating ring attached to said member from said portion of said tamper indicating ring attached to said arcuate projection;

wherein said tamper indicating ring includes an elevated area extending axially towards said depending skirt, wherein said elevated area defines a region of decreased ring spacing from said depending skirt.

3. The tamper indicating closure of Claim ~~2~~ 1 or 25, further comprising a plurality of said frangible elements and said elevated areas, wherein at least one of said frangible elements is connected to said depending skirt between two said elevated areas.

9 The tamper indicating closure of Claim 1 or 25, wherein said inner annular sealing flange includes at least one annular sealing bead extending around ~~a portion of~~ said inner annular sealing flange and being configured for engagement with the interior surface of said container neck finish.

10. The tamper indicating closure of Claim 8, wherein said inner annular sealing flange includes at least one annular sealing bead extending around ~~a portion of~~ said inner annular sealing flange and being configured for engagement with the interior surface of said container neck finish.

11 The tamper indicating closure of Claim 1 or 25, wherein said annular depending skirt includes at least one annular sealing bead extending around ~~a portion of~~ said skirt and being configured for engagement with the exterior surface of said container neck finish.

12 The tamper indicating closure of Claim 10, wherein said annular depending skirt includes at least one annular sealing bead extending around ~~a portion of~~ said skirt and being configured for engagement with the exterior surface of said container neck finish.

25. A tamper indicating closure configured for snap-on or screw-on application to a container, said closure and container comprising in combination:

- a. a closure top portion;
- b. an annular depending skirt extending from said top portion, said depending skirt having an internal thread configuration adapted for engaging an external thread configuration on the neck portion of said container by snap-on application during initial installation of said closure to said container neck;
- c. an inner annular sealing flange depending from said closure top portion in spaced relation to said depending skirt; and
- d. a tamper indicating ring connected to said depending skirt by a plurality of frangible elements;

wherein said tamper indicating ring includes at least one arcuate projection extending around at least a portion of said tamper indicating ring arranged for registration with a container neck portion on which said closure is positioned and said closure includes at least one nonremovable member breakably attached to said tamper-indicating ring which cooperates with

at least one said arcuate projection to assist in breaking said tamper indicating ring during removal of said closure from said container neck.; and

wherein at least one said arcuate projection is held in place by an annular locking flange on said container neck as said member is pulled away from said arcuate projection by twist-off removal of said annular depending skirt to cause said tamper indicating ring to break at a weakened area as said member pulls said tamper indicating ring upward to cause breakage of said frangible elements connecting said skirt to said tamper indicating ring and fracture of said weakened area by separation of said portion of said tamper indicating ring attached to said member from said portion of said tamper indicating ring attached to said arcuate projection;

wherein said tamper indicating ring includes an elevated area extending axially towards said depending skirt, wherein said elevated area defines a region of decreased ring spacing from said depending skirt.

REMARKS

Applicant respectfully submits that the foregoing amendments are sufficient to place the application in a condition for allowance.

Objections to the Drawings and Specification:

It is respectfully submitted that the cancellation of Claims 13 and 15 is sufficient to overcome the Examiner's objections to the drawings and corresponding objection to the